



Zuleitung H05VV-F 3G1,5 mm² schwarz mit IEC C20 Stecker

<p>19" 1HE 9xIEC320 C13 Kaltgerätesteckdosen Länge 438,5mm</p> <p>IEC320 C13 Steckdosen</p> <ul style="list-style-type: none"> • nach DIN 49 440, geprüft nach: VDE0620-1; • 2-polig mit Schutzkontakt; • 10A/2300W, AC250V, IP20 <p>Anschluss:</p> <ul style="list-style-type: none"> • Nicht wiederanschließbar; Endstücke genietet, Innenverdrahtung ohne Euroklemme • 2,0m H05VV-F 3G1,5mm² schwarz mit C20 Stecker <p>Profil:</p> <ul style="list-style-type: none"> • 1HE, ALU, eloxiert; <p>Kunststoff:</p> <ul style="list-style-type: none"> • RAL7035, PA6, Glasfaser 30%, Glühdrahtprüfung bis 850°C; V1 <p>Haltewinkel:</p> <ul style="list-style-type: none"> • Stahlblech • Montage in 90° - Schritten möglich; <p>Lieferform:</p> <ul style="list-style-type: none"> • Polybeutel mit Bachmann Reiter • mit Bachmann Art.-Nr. und Barcode 13 <p>Lieferumfang:</p> <ul style="list-style-type: none"> • 1 x Steckdosenleiste • 2 x 19" Befestigungswinkel inkl. 8 Schrauben (im Polybeutel) 	<p>19" 1U 9xIEC320 C13 sockets Length 438,5mm</p> <p>IEC320 C13 Sockets:</p> <ul style="list-style-type: none"> • DIN 49 440, tested: VDE0620-1; • 2-pole with earthing contact; • 10A/2300W, AC250V, IP20, <p>Connection:</p> <ul style="list-style-type: none"> • Not rewireable, Endcaps riveted, inside wiring without euro terminal • 2,0m H05VV-F 3G1,5mm² black with C20 plug <p>Profile:</p> <ul style="list-style-type: none"> • 1U, ALU, anodized <p>Plastic material:</p> <ul style="list-style-type: none"> • RAL7035, PA6, fibre glass 30%, Glow wire test up to 850° C ; V1 <p>Mounting brackets:</p> <ul style="list-style-type: none"> • Steel sheet • For fixing in 4 positions each 90° <p>Packing:</p> <ul style="list-style-type: none"> • polybag with Bachmann header • With Bachmann Item no. and bar code 13 <p>Extent of delivery:</p> <ul style="list-style-type: none"> • 1 x Socket strip • 2 x 19" mounting brackets incl. 8 screws (in polybag)
--	--