



NOTE:

- 1.ELECTRICAL TEST:100% OPEN SHORT, MISS WIRE TEST
- 2.FLUKE Channel LINK TEST:
TEST LIMIT:ISO11801 Channel Class EA
- 3.Storage temperature:-10°C~+60°C
Working temperature:-20°C~+75°C
- 4.RoHS2.0 AND REACH compliant
- 5.Spray WORD:CAT6A S/FTP 4x2x28AWG/7 LSZH ISO11801 &EN50173 & ANSI/TIA 568.2-D
- 6.Support PoE per IEEE 802.3af,PoE+ per IEEE 802.3at, PoE++ per IEEE 802.3bt
- 7.Minimum of the bending radius is 6*ODmm(Suitable for all meters)

MATERIAL LIST:

③	OVER MOLD	75A PVC Gray(RAL 7035)	2	
②	PLUG	RJ45 8P8C SHIELDED Plug PIN GOLD PLATED 3U",THE SHELL PLATED NICKEL, COLOUR:TRANSPARENT BLUE	2	
①	CABLE	S/FTP CAT. 6A 28AWG (BC+AL-FOIL)*4P+BRAID(AL-MG) JACKET:Gray(RAL 7035) LSZH OD:4.5±0.2mm	1	
NO.	PARTS NAME	SPECIFICATION STANDARD	QT' Y	REMARK

21.15.4318	ROLINE PatchCord S/FTP(PiMF) Cat.6A Slim, DATACENTER, LSOH, tangle free, 0.3m	300±10
21.15.4310	ROLINE PatchCord S/FTP(PiMF) Cat.6A Slim, DATACENTER, LSOH, tangle free, 0.5m	500±15
21.15.4311	ROLINE PatchCord S/FTP(PiMF) Cat.6A Slim, DATACENTER, LSOH, tangle free, 1m	1000±20
21.15.4314	ROLINE PatchCord S/FTP(PiMF) Cat.6A Slim, DATACENTER, LSOH, tangle free, 1.5m	1500±30
21.15.4312	ROLINE PatchCord S/FTP(PiMF) Cat.6A Slim, DATACENTER, LSOH, tangle free, 2m	2000±30
21.15.4313	ROLINE PatchCord S/FTP(PiMF) Cat.6A Slim, DATACENTER, LSOH, tangle free, 3m	3000±50
21.15.4315	ROLINE PatchCord S/FTP(PiMF) Cat.6A Slim, DATACENTER, LSOH, tangle free, 5m	5000±100
21.15.4316	ROLINE PatchCord S/FTP(PiMF) Cat.6A Slim, DATACENTER, LSOH, tangle free, 7m	7000±200
21.15.4317	ROLINE PatchCord S/FTP(PiMF) Cat.6A Slim, DATACENTER, LSOH, tangle free, 10m	10000±200
ITEM NO.	DESC.	LENGTH

		NEW	2024-06-25	A
BY	CHK	REVISION RECORD MODIFICATIONS	DATE	REV.

