


WIRING DIAGRAM



NOTE:

- ELECTRICAL TEST:100% OPEN SHORT, MISS WIRE TEST
- FLUKE Channel LINK TEST:  
TEST LIMIT:ISO11801 Channel Class EA
- Working temperature:-20°C~+75°C  
Storage temperature:-20°C~+80°C
- RoHS AND REACH compliant
- Spray WORD:CAT6A S/FTP with 600MHz cat.7 raw cable  
4x2x26AWG/7 RECYCLED TPE ISO11801 & EN50173 & ANSI/TIA568.2-D
- Minimum of the bending radius is 4\*OD (Suitable for all meters)

21.45.3249	ROLINE RECYCLED S/FTP PatchCord Cat6A/C1.EA, TPE, blue, 20m	20000±300	53.40%
21.45.3248	ROLINE RECYCLED S/FTP PatchCord Cat6A/C1.EA, TPE, blue, 15m	15000±300	53.40%
21.45.3247	ROLINE RECYCLED S/FTP PatchCord Cat6A/C1.EA, TPE, blue, 10m	10000±300	53.40%
21.45.3246	ROLINE RECYCLED S/FTP PatchCord Cat6A/C1.EA, TPE, blue, 7m	7000±150	53.30%
21.45.3245	ROLINE RECYCLED S/FTP PatchCord Cat6A/C1.EA, TPE, blue, 5m	5000±100	53.30%
21.45.3243	ROLINE RECYCLED S/FTP PatchCord Cat6A/C1.EA, TPE, blue, 3m	3000±50	53.10%
21.45.3242	ROLINE RECYCLED S/FTP PatchCord Cat6A/C1.EA, TPE, blue, 2m	2000±30	53.00%
21.45.3244	ROLINE RECYCLED S/FTP PatchCord Cat6A/C1.EA, TPE, blue, 1.5m	1500±30	52.90%
21.45.3241	ROLINE RECYCLED S/FTP PatchCord Cat6A/C1.EA, TPE, blue, 1m	1000±20	52.60%
21.45.3240	ROLINE RECYCLED S/FTP PatchCord Cat6A/C1.EA, TPE, blue, 0.5m	500±20	52.10%
21.45.3274	ROLINE RECYCLED S/FTP PatchCord Cat6A/C1.EA, TPE, blue, 0.3m	300±10	51.70%
ITEM NO.	DESC.	LENGTH (mm)	The proportion of RECYCLED certification materials

MATERIAL LIST:

③	OVER MOLD	RECYCLED PVC BLUE PANTONE 647C	2	
②	PLUG	RJ45 8P8C SHIELDED PLUG PIN GOLD PLATED 3U", THE SHELL PLATED NICKEL, COLOUR: TRANSPARENT GREEN	2	
①	CABLE	S/FTP CAT. 7 26AWG (BC+RECYCLED INSULATION+AL-FOIL)*4P+ BRAID (AL-MG) JACKET: RECYCLED TPE BLUE PANTONE 647C OD: 6.0±0.2MM	1	
NO.	PARTS NAME	SPECIFICATION DESCRIPTION	QT'Y	REMARK
		NEW	2023-11-30	A
BY	CHK	REVISION RECORD MODIFICATIONS	DATE	REV.

