



* Endstücke genietet * Endcaps riveted * Embouts riveter

12x IEC320 C19	12x IEC320 C19	12x IEC 320 C19
Steckdosen: <ul style="list-style-type: none"> Nach IEC320 C19 2-polig mit Schutzkontakt; 16A/3680W, AC250V, IP20, Schwarz in Abdeckung RAL7035 	Sockets: <ul style="list-style-type: none"> IEC 320 C19 2-pole with earthing contact; 16A/3680W, AC250V, IP20, black in part RAL7035 	Prises: <ul style="list-style-type: none"> IEC 320 C19 2 pôles, 1 prise de terre 16A/3680W, AC250V, IP20, noir in plastic RAL7035
Anschluss: <ul style="list-style-type: none"> nicht wiederanschließbar; 2m H05VV-F 3G1,5mm² mit CEE 16A 	Connection: <ul style="list-style-type: none"> not rewireable, 2m H05VV-F 3G1,5mm² with CEE 16A 	Connection: <ul style="list-style-type: none"> non Reconnection possible 2m H05VV-F 3G1,5mm² par CEE 16A
Profil: 1HE, ALU, eloxiert;	Body: 1HE, ALU, anodized	Profilé: 1U, ALU, anodisé
Kunststoff: <ul style="list-style-type: none"> RAL7035, PA6, Glasfaser 30%, Glühdrahtprüfung bis 850°C; V1 	Plastic parts: <ul style="list-style-type: none"> RAL7035, PA6, fibre glass 30%, Glow wire test up to 850°C ; V1 	Éléments plastiques: <ul style="list-style-type: none"> RAL7035, PA6, fibre de verre 30%, test au fil incandescent : jusqu'à 850°C ; V1
Haltewinkel: <ul style="list-style-type: none"> Für vertikale Montage, Artikelnr. 20110-068 separat bestellen. 	Brackets: <ul style="list-style-type: none"> For vertical fitting, item no. 20110-068, to order separately. 	Equerres: <ul style="list-style-type: none"> Montage vertical avec : réf. 20110-068, à commander séparément.
Lieferform: <ul style="list-style-type: none"> Neutrale Kartonverpackung mit Schroff Art.-Nr. und Barcode 39 	Form of delivery: <ul style="list-style-type: none"> Neutral carton box With Schroff Item no. and bar code 39 	Conditionnement : <ul style="list-style-type: none"> Emballage dans carton neutre Avec réf. Schroff et code barre 39
Lieferumfang: <ul style="list-style-type: none"> 1 x Steckdosenleiste 	Extent of delivery: <ul style="list-style-type: none"> 1 x Socket strip 	Composition : <ul style="list-style-type: none"> 1 x Bâti de prises
Thermische Eigenschaften <ul style="list-style-type: none"> Betriebs- Umgebungstemperatur 0 ... +55°C Lagertemperatur -20... +75°C Betriebs-Umgebungsfeuchte 5... 95% nicht kondensierend 	Thermal specifications <ul style="list-style-type: none"> Operating temperature range 0...+55°C Storage temperature range -20... +75°C Operating humidity range 5...95% relative humidity, non-condensing 	Spécification thermiques <ul style="list-style-type: none"> Temperature de fonctionnement 0°:+55° Temperature de stockage -20°... +75° Humidité en fonctionnement 5°... 95% sans condensation