

Brother TD-2130NXX1 label printer Direct thermal 300 x 300 DPI 152.4 mm/sec Ethernet LAN

Brand : Brother

Product code: TD-2130NXX1

Product name : TD-2130NXX1

203x203 dpi, 152.4 mm/sec, USB, RS-232C, LAN

Brother TD-2130NXX1 label printer Direct thermal 300 x 300 DPI 152.4 mm/sec Ethernet LAN:

There's nothing more powerful than having exactly the right tool for the job - which is why we're delighted to introduce the flexible new TD-2130N. Boasting a wealth of specialised features, including generous 5" roll size, ZPL II emulation and impressive memory - all of which make it ideally suited to warehousing, logistics, manufacturing and more - the TD2130N also includes network capability and increased resolution of 300dpi. Brother TD-2130NXX1. Print technology: Direct thermal, Maximum resolution: 300 x 300 DPI, Print speed: 152.4 mm/sec. Product colour: White



Printing		Design	
Print technology *	Direct thermal	Product colour *	White
Maximum resolution *	300 x 300 DPI	System requirements	
Print speed *	152.4 mm/sec	Windows operating systems supported	✓
Maximum printing width *	5.6 cm	Operational conditions	
Maximum print height	9.86 cm	Operating relative humidity (H-H)	20 - 80%
Vertical printing	✓	Storage relative humidity (H-H)	20 - 80%
Paper handling		Operating temperature (T-T)	5 - 40 °C
Autocutter	✓	Storage temperature (T-T)	-20 - 60 °C
Maximum label length	1 m	Weight & dimensions	
Ports & interfaces		Width	110 mm
Ethernet LAN *	✓	Depth	215 mm
USB port *	✓	Height	172 mm
USB 2.0 ports quantity	1	Weight	1.34 kg
RS-232 ports	1	Packaging content	
Optional connectivity	Ethernet, Serial (RS-232), USB 2.0	Cables included	USB
Performance		Drivers included	✓
Flash memory	6 MB	Logistics data	
Built-in barcodes	CODABAR (NW-7), Code 128 (A/B/C), Code 39, Code 93, Code-128 Codabar Library, Data Matrix, EAN128, EAN13, EAN8, GS1-128, ITF, MaxiCode, Micro QR Code, MicroPDF417, PDF417, POSTNET, QR Code, UPC-A, UPC-E	Harmonized System (HS) code	84433210
Number of fonts	10	Other features	
Tape cutting	Automatic	Character sets	Abicomp, ASCII, BRASCII, ISO 8859-15, ISO Latin 1, Italic, PC437, PC850, PC858, PC860, PC861, PC863, PC865, Roman 8
Underline	✓		

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 21-FEB-2024. Prints or copies of Information are only valid on the printed Publication date