



TP-Link ER7412-M2 bedrade router 2.5 Gigabit Ethernet, Gigabit Ethernet Zwart

Merk : TP-Link

Artikelcode: ER7412-M2

Productnaam : ER7412-M2



TP-Link ER7412-M2. Netwerkstandaard: IEEE 802.1Q, IEEE 802.3, IEEE 802.3ab, IEEE 802.3u, IEEE 802.3x, IEEE 802.3z, Ethernet interface type: 2.5 Gigabit Ethernet, Gigabit Ethernet, Ethernet LAN, data-overdrachtsnelheden: 10,100,1000,2500 Mbit/s. Ondersteunde beveiligingsalgoritmen: 128-bit AES, 192-bit AES, 256-bit AES, DES, MD5, SHA-1, SHA-2, SHA-384, SHA-512. Flash memory: 128 MB, Intern geheugen: 1024 MB, Intern geheugentype: DDR4. Kleur van het product: Zwart. Vermogensverbruik (max): 18,5 W, AC-ingangsspanning: 100 - 240 V, AC-ingangsfrequentie: 50/60 Hz

WAN-verbinding		Beveiliging	
Ethernet WAN *	✓	Access Control List (ACL)	✓
DSL WAN *	✗	Network address translation (NAT)	✓
SIM-kaartsleuf *	✗	VPN tunnels quantity	80
3G/4G USB modem compatibiliteit *	✓	Technische details	
SFP WAN *	✓	Certificaten van naleving	CE, Federal Communications Commission (FCC)
Netwerk		Kenmerken	
Netwerkstandaard *	IEEE 802.1Q, IEEE 802.3, IEEE 802.3ab, IEEE 802.3u, IEEE 802.3x, IEEE 802.3z	Flash memory	128 MB
Ethernet interface type *	2.5 Gigabit Ethernet, Gigabit Ethernet	Intern geheugen	1024 MB
Ethernet LAN, data-overdrachtsnelheden	10,100,1000,2500 Mbit/s	Intern geheugentype	DDR4
Statische route	✓	Ondersteunt Windows	Windows 10, Windows 11, Windows 2000, Windows 7, Windows 8, Windows 8.1, Windows 98SE, Windows NT, Windows Vista, Windows XP
VLAN=ondersteuning	✓	Ondersteunt Mac-besturingssysteem	✓
Beheerfuncties		Ondersteunt Linux	✓
Web-gebaseerd management *	✓	Design	
Universal Plug and Play (UPnP)	✓	Kleur van het product *	Zwart
Reset button	✓	Rack-montage	✓
Poorten & interfaces		Energie	
Aantal Ethernet LAN (RJ-45)-poorten *	10	Vermogensverbruik (max)	18,5 W
Aantal moduleslots SPF	2	AC-ingangsspanning	100 - 240 V
Aantal consolepoorten	1	AC-ingangsfrequentie	50/60 Hz
Aantal USB-aansluitingen	1	Eisen aan de omgeving	
Protocollen		Bedrijfstemperatuur (T-T)	0 - 45 °C
DMZ support	✓	Temperatuur bij opslag	-40 - 70 °C
DHCP server *	✓	Relatieve vochtigheid in bedrijf (V-V)	10 - 90 procent
Beveiliging		Luchtvochtigheid bij opslag	5 - 90 procent
Ondersteunde beveiligingsalgoritmen *	128-bit AES, 192-bit AES, 256-bit AES, DES, MD5, SHA-1, SHA-2, SHA-384, SHA-512		

Beveiliging		Gewicht en omvang	
URL- filtering	✓	Breedte	294 mm
DoS aanval preventie	✓	Diepte	180 mm
ARP-aanvalspreventie	✓	Hoogte	44 mm
ICMP-aanvalspreventie	✓		
Verpakking			
Meegeleverde kabels			AC, LAN (RJ-45)
Snelstartgids			✓



4895252505184

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 05-AUG-2024. Prints or copies of Information are only valid on the printed Publication date