



TP-Link ER7406 bedrade router Gigabit Ethernet Zwart

Merk : TP-Link

Artikelcode: ER7406

Productnaam : ER7406

TP-Link ER7406. Netwerkstandaard: IEEE 802.1D, IEEE 802.3, IEEE 802.3ab, IEEE 802.3u, IEEE 802.3x, IEEE 802.3z, Ethernet interface type: Gigabit Ethernet, Ethernet LAN, data-overdrachtsnelheden: 10,100,1000 Mbit/s. Ondersteunde beveiligingsalgoritmen: 128-bit AES, 192-bit AES, 256-bit AES, DES, MD5, SHA-1, SHA-2, SHA-384, SHA-512. Flash memory: 128 MB, Intern geheugen: 512 MB, Intern geheugentype: DDR4. Kleur van het product: Zwart. Vermogensverbruik (max): 7,5 W, AC-ingangsspanning: 100 - 240 V, AC-ingangsfrequentie: 50/60 Hz



WAN-verbinding		Beveiliging	
Ethernet WAN *	✓	VPN tunnels quantity	50
DSL WAN *	✗	Technische details	
SIM-kaartsleuf *	✗	Certificaten van naleving	CE, Federal Communications Commission (FCC), RoHS
3G/4G USB modem compatibiliteit *	✓	Kenmerken	
SFP WAN *	✓	Flash memory	128 MB
Netwerk		Intern geheugen	512 MB
Netwerkstandaard *	IEEE 802.1D, IEEE 802.3, IEEE 802.3ab, IEEE 802.3u, IEEE 802.3x, IEEE 802.3z	Intern geheugentype	DDR4
Ethernet interface type *	Gigabit Ethernet	Ondersteunt Windows	Windows 10, Windows 2000, Windows 7, Windows 8, Windows 8.1, Windows 98SE, Windows NT, Windows Vista, Windows XP
Ethernet LAN, data-overdrachtsnelheden	10,100,1000 Mbit/s	Ondersteunt Mac-besturingssysteem	✓
Statische route	✓	Ondersteunt Linux	✓
VLAN=ondersteuning	✓	Design	
Beheerfuncties		Kleur van het product *	Zwart
Web-gebaseerd management *	✓	Rack-montage	✓
Reset button	✓	Energie	
Poorten & interfaces		Vermogensverbruik (max)	7,5 W
Aantal Ethernet LAN (RJ-45)-poorten *	5	AC-ingangsspanning	100 - 240 V
Aantal geïnstalleerde SFP modules	1	AC-ingangsfrequentie	50/60 Hz
Aantal USB-aansluitingen	1	Eisen aan de omgeving	
Protocollen		Bedrijfstemperatuur (T-T)	0 - 50 °C
DMZ support	✓	Temperatuur bij opslag	-40 - 70 °C
DHCP server *	✓	Relatieve vochtigheid in bedrijf (V-V)	10 - 90 procent
Beveiliging		Luchtvochtigheid bij opslag	5 - 90 procent
Ondersteunde beveiligingsalgoritmen *	128-bit AES, 192-bit AES, 256-bit AES, DES, MD5, SHA-1, SHA-2, SHA-384, SHA-512	Gewicht en omvang	
URL- filtering	✓	Breedte	294 mm
DoS aanval preventie	✓	Diepte	140 mm
ARP-aanvalspreventie	✓		

Beveiliging		Gewicht en omvang	
ICMP-aanvalspreventie	✓	Hoogte	44 mm
Verpakking		Meegeleverde kabels	AC
		Snelle installatiehandleiding	✓



8885020622300

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 23-AUG-2024. Prints or copies of Information are only valid on the printed Publication date