

TP-Link TL-R470T+ bedrade router Fast Ethernet Zwart

Merk : TP-Link

Artikelcode: TL-R470T+

Productnaam : TL-R470T+



TP-Link TL-R470T+. Netwerkstandaard: IEEE 802.3, IEEE 802.3u, IEEE 802.3x, Ethernet interface type: Fast Ethernet, Bekabelingstechnologie: 10/100Base-T(X). Ondersteunde netwerkprotocollen: TCP/IP, DHCP, ICMP, NAT, PPPoE, SNTP, HTTP, DNS. Ondersteunde beveiligingsalgoritmen: HTTPS, VPN eigenschappen: PPTP/L2TP/IP Sec. Flash memory: 16 MB, Intern geheugen: 128 MB, Ondersteunt Windows: Windows 7, Windows 8, Windows Vista, Windows XP. Kleur van het product: Zwart, LED-indicatoren: LAN, Stroom, Systeem, WAN, WLAN

WAN-verbinding		Beveiliging	
Ethernet WAN *	✓	MAC adres filtering	✓
Netwerk		IP-MAC-Port binding	✓
Netwerkstandaard *	IEEE 802.3, IEEE 802.3u, IEEE 802.3x	VPN eigenschappen	PPTP/L2TP/IP Sec
Ethernet interface type *	Fast Ethernet	Kenmerken	
Bekabelingstechnologie	10/100Base-T(X)	Flash memory	16 MB
Ethernet LAN, data-overdrachtsnelheden	10,100 Mbit/s	Intern geheugen	128 MB
Full duplex	✗	Ondersteunt Windows	Windows 7, Windows 8, Windows Vista, Windows XP
Statische route	✓	Ondersteunt Mac-besturingssysteem	macOS
Verkeerscontrole	✓	Ondersteunt Linux	✓
Concurrent connections	10000	Warmtedissipatie	1 BTU/h
Beheerfuncties		Mean time between failures (MTBF)	1 uur
Web-gebaseerd management *	✓	Certificering	CE, FCC, RoHS
Quality of Service (QoS)	✓	Design	
Universal Plug and Play (UPnP)	✓	Kleur van het product *	Zwart
Reset button	✓	Rack-montage	✗
Poorten & interfaces		LED-indicatoren	LAN, Stroom, Systeem, WAN, WLAN
Aantal Ethernet LAN (RJ-45)-poorten *	4	Energie	
Fibre channel-poorten	1	Stroomverbruik (typisch) *	1,56 W
Protocollen		Eisen aan de omgeving	
DMZ support	✓	Bedrijfstemperatuur (T-T)	0 - 40 °C
DHCP client *	✓	Temperatuur bij opslag	-40 - 70 °C
DHCP server *	✓	Relatieve vochtigheid in bedrijf (V-V)	10 - 90 procent
Ondersteunde netwerkprotocollen	TCP/IP, DHCP, ICMP, NAT, PPPoE, SNTP, HTTP, DNS	Luchtvochtigheid bij opslag	5 - 90 procent
Beveiliging		Gewicht en omvang	
Ondersteunde beveiligingsalgoritmen *	HTTPS	Breedte	158 mm
Firewall	✓	Diepte	101 mm
		Hoogte	25 mm

Overige specificaties

Switch type

Unmanaged

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 17-JUN-2024. Prints or copies of Information are only valid on the printed Publication date