

TP-Link TL-SL1226P Unmanaged Gigabit Ethernet (10/100/1000) Power over Ethernet (PoE) 1U Grijs

Merk : TP-Link

Artikelcode: TL-SL1226P V1

Productnaam : TL-SL1226P



TP-Link TL-SL1226P. Switch type: Unmanaged. Type basis-switching RJ-45 Ethernet-poorten: Gigabit Ethernet (10/100/1000), Aantal basis-switching RJ-45 Ethernet-poorten: 26. MAC-adrestabel: 8000 entries, Switchingcapaciteit: 8,8 Gbit/s. Netwerkstandaard: IEEE 802.3af, IEEE 802.3at, IEEE 802.3x. Power over Ethernet (PoE). Rack-montage, Vormfactor: 1U

Beheerfuncties		Energie	
Switch type *	Unmanaged	Stroombron *	AC
Poorten & interfaces		Vermogenstoevoer inclusief *	✓
Aantal basis-switching RJ-45 Ethernet-poorten *	26	AC-ingangsspanning	100 - 240 V
Type basis-switching RJ-45 Ethernet-poorten *	Gigabit Ethernet (10/100/1000)	AC-ingangsfrequentie	50 - 60 Hz
Fast Ethernet (koperen) ports kwantiteit	24	Vermogensverbruik (max)	281 W
Aantal Gigabit Ethernet (koper)-poorten	2	Power over Ethernet (PoE)	
Aantal Combo SFP-poorten	2	Power over Ethernet (PoE) *	✓
Netwerk		Aantal Power over Ethernet plus (PoE +)-poorten	24
Netwerkstandaard *	IEEE 802.3af, IEEE 802.3at, IEEE 802.3x	Vermogen per poort Power over Ethernet (PoE)	30 W
10G support *	✗	Totaal Power over Ethernet (PoE)-budget	250 W
Koperen ethernetbekabelingstechnologie	10BASE-T, 100BASE-TX, 1000BASE-T	Eisen aan de omgeving	
Auto MDI/MDI-X	✓	Bedrijfstemperatuur (T-T)	0 - 50 °C
Auto-negotiation	✓	Temperatuur bij opslag	-40 - 70 °C
Data-uitwisseling		Relatieve vochtigheid in bedrijf (V-V)	10 - 90 procent
Switchingcapaciteit *	8,8 Gbit/s	Luchtvochtigheid bij opslag	5 - 90 procent
Verzending snelheid	6,54 Mpps	Warmtedissipatie	1002,54 BTU/h
MAC-adrestabel *	8000 entries	Gewicht en omvang	
Store-and-forward	✓	Breedte	440 mm
Jumbo Frames ondersteuning	✓	Diepte	180 mm
Jumbo frames	10000	Hoogte	44 mm
Packet buffergeheugen	4,1 MB	Verpakking	
Design		Snelstartgids	✓
Rack-montage *	✓	Rekbevestigingspakket	✓
Vormfactor	1U	Breedte verpakking	528 mm
Kleur van het product	Grijs	Diepte verpakking	250 mm
LED-indicatoren	✓	Hoogte verpakking	80 mm
Aantal ventilatoren	2 ventilator(en)	Logistieke gegevens	
Certificering	CE, FCC, RoHS	Code geharmoniseerd systeem (HS)	85176990



6935364089443



6935364089450



0845973089443



845973089443

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.