


## TP-Link TL-SG1005LP netwerk-switch Unmanaged Gigabit Ethernet (10/100/1000) Power over Ethernet (PoE) Zwart

**Merk :** TP-Link

**Artikelcode:** TL-SG1005LP

**Productnaam :** TL-SG1005LP

TP-Link TL-SG1005LP. Switch type: Unmanaged. Type basis-switching RJ-45 Ethernet-poorten: Gigabit Ethernet (10/100/1000), Aantal basis-switching RJ-45 Ethernet-poorten: 5. MAC-adrestabel: 2000 entries, Switchingcapaciteit: 10 Gbit/s. Netwerkstandaard: IEEE 802.1p, IEEE 802.3ab, IEEE 802.3af, IEEE 802.3at, IEEE 802.3i, IEEE 802.3u, IEEE 802.3x. Power over Ethernet (PoE). Ophangstelsysteem voor aan de muur



<b>Beheerfuncties</b>		<b>Design</b>	
Switch type *	Unmanaged	LED-indicatoren	✓
Quality of Service (QoS)	✓	Ophangstelsysteem voor aan de muur	✓
<b>Poorten &amp; interfaces</b>		Certificering	FCC, CE, RoHS
Aantal basis-switching RJ-45 Ethernet-poorten *	5	<b>Prestatie</b>	
Type basis-switching RJ-45 Ethernet-poorten *	Gigabit Ethernet (10/100/1000)	Fanloos	✓
<b>Netwerk</b>		<b>Energie</b>	
Netwerkstandaard *	IEEE 802.1p, IEEE 802.3ab, IEEE 802.3af, IEEE 802.3at, IEEE 802.3i, IEEE 802.3u, IEEE 802.3x	Vermogenstoevoer inclusief *	✓
10G support *	✗	AC-ingangsspanning	100 - 240 V
Koperen ethernetbekabelingstechnologie	10BASE-T, 100BASE-TX, 1000BASE-T	AC-ingangsfrequentie	50 - 60 Hz
Ondersteunde kabel types	Cat3, Cat4, Cat5, Cat5e, Cat6	Vermogensverbruik (max)	47,5 W
Datastroombeheer	✓	<b>Power over Ethernet (PoE)</b>	
Auto MDI/MDI-X	✓	Power over Ethernet (PoE) *	✓
Auto-negotiation	✓	Aantal Power over Ethernet plus (PoE +)-poorten	4
MAC-adres zelflerende functie	✓	Totaal Power over Ethernet (PoE)-budget	40 W
MAC-adres zelfverouderende functie	✓	<b>Eisen aan de omgeving</b>	
<b>Data-uitwisseling</b>		Bedrijfstemperatuur (T-T)	0 - 40 °C
Switchingcapaciteit *	10 Gbit/s	Temperatuur bij opslag	-40 - 70 °C
Verzending snelheid	7,44 Mpps	Relatieve vochtigheid in bedrijf (V-V)	10 - 90 procent
MAC-adrestabel *	2000 entries	Luchtvochtigheid bij opslag	5 - 90 procent
Store-and-forward	✓	Warmtedissipatie	161,98 BTU/h
Jumbo Frames ondersteuning	✓	<b>Gewicht en omvang</b>	
Jumbo frames	16000	Breedte	99,8 mm
<b>Beveiliging</b>		Diepte	98 mm
IGMP snooping	✓	Hoogte	25 mm
<b>Design</b>		<b>Verpakking</b>	
Rack-montage *	✗	Gebruiksaanwijzing	✓
Kleur van het product	Zwart		

**Logistieke gegevens**

Code geharmoniseerd systeem (HS) 85176990



6935364052737



6935364052720

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 31-MAY-2023. Prints or copies of Information are only valid on the printed Publication date