



## TP-Link TL-SG2218P netwerk-switch L2/L2+ Gigabit Ethernet (10/100/1000) Power over Ethernet (PoE) 1U Zwart

**Merk :** TP-Link

**Artikelcode:** TL-SG2218P

**Productnaam :** TL-SG2218P



TP-Link TL-SG2218P. Switch-laag: L2/L2+. Type basis-switching RJ-45 Ethernet-poorten: Gigabit Ethernet (10/100/1000), Aantal basis-switching RJ-45 Ethernet-poorten: 16. MAC-adrestabel: 8000 entries, Switchingcapaciteit: 26,78 Gbit/s. Netwerkstandaard: IEEE 802.1D, IEEE 802.1Q, IEEE 802.1p, IEEE 802.1s, IEEE 802.1w, IEEE 802.1x, IEEE 802.3ab, IEEE.... Power over Ethernet (PoE). Rack-montage, Vormfactor: 1U

Beheerfuncties		Beveiliging	
Switch-laag	L2/L2+	Access Control List (ACL)	✓
Quality of Service (QoS)	✓	MAC adres filtering	✓
Web-gebaseerd management	✓	Statische poort beveiliging	✓
Cloud-beheerd	✓	SSH/SSL support	✓
ARP-inspectie	✓	Bescherming lus	✓
Locatie-instellingen (CLI) configureren	✓	BPDU filtering / bescherming	✓
System event log	✓	Authenticatie	MAC-gebaseerde authenticatie, Poortgebaseerde authenticatie
MIB-ondersteuning	MIB II (RFC1213), Bridge MIB (RFC1493), P/Q-Bridge MIB (RFC2674), Radius Accounting Client MIB (RFC2620), Radius Authentication Client MIB (RFC2618), Remote Ping, Traceroute MIB (RFC2925), Support TP-Link private MIBs, RMON MIB(RFC1757, rmon 1,2,3,9)	Multicast-functies	
		Multicast-ondersteuning	✓
		Multicast-functies	Multicast-doorsturen
Poorten & interfaces		Design	
Aantal basis-switching RJ-45 Ethernet-poorten *	16	Rack-montage *	✓
Type basis-switching RJ-45 Ethernet-poorten *	Gigabit Ethernet (10/100/1000)	Vormfactor	1U
Netwerk		Kleur van het product	Zwart
Netwerkstandaard *	IEEE 802.1D, IEEE 802.1Q, IEEE 802.1p, IEEE 802.1s, IEEE 802.1w, IEEE 802.1x, IEEE 802.3ab, IEEE 802.3ad, IEEE 802.3az, IEEE 802.3i, IEEE 802.3u, IEEE 802.3x, IEEE 802.3z	LED-indicatoren	✓
10G support *	✗	Certificering	CE, FCC, RoHS
IP routing	✓	Energie	
Op beleid gebaseerde routing	✓	Stroombron *	DC/PoE
Datastroombeheer	✓	Vermogenstoevoer inclusief *	✓
Verbindingsaggregatie	✓	AC-ingangsspanning	100 - 240 V
Broadcast stormbeheer	✓	AC-ingangsfrequentie	50 - 60 Hz
Rate limiting	✓	Power over Ethernet (PoE)	
Auto MDI/MDI-X	✓	Power over Ethernet (PoE) *	✓
Spanning tree protocol	✓	Totaal Power over Ethernet (PoE)-budget	150 W
Ethernet LAN, data-overdrachtsnelheden	10,100,1000 Mbit/s	Eisen aan de omgeving	
Auto-negotiation	✓	Bedrijfstemperatuur (T-T)	0 - 50 °C
VLAN=ondersteuning	✓	Temperatuur bij opslag	-40 - 70 °C
Data-uitwisseling		Relatieve vochtigheid in bedrijf (V-V)	10 - 90 procent
Switchingcapaciteit *	26,78 Gbit/s	Luchtvochtigheid bij opslag	5 - 90 procent
Verzending snelheid	26,78 Mpps	Gewicht en omvang	
MAC-adrestabel *	8000 entries	Breedte	440 mm
		Diepte	180 mm
		Hoogte	44 mm
		Verpakking	
		Meegeleverde kabels	LAN (RJ-45)
		Gebruiksaanwijzing	✓
		Type verpakking	Doos

**Data-uitwisseling**

Jumbo Frames ondersteuning	✓
Jumbo frames	9

**Beveiliging**

DHCP-functies	DHCP client, DHCP relay, DHCP snooping
---------------	--



4897098689516



4897098689509



0840030709500



840030709500

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.