



TP-Link TL-SG116P netwerk-switch Unmanaged Gigabit Ethernet (10/100/1000) Zwart

Merk : TP-Link

Artikelcode: TL-SG116P

Productnaam : TL-SG116P



TP-Link TL-SG116P. Switch type: Unmanaged. Type basis-switching RJ-45 Ethernet-poorten: Gigabit Ethernet (10/100/1000), Aantal basis-switching RJ-45 Ethernet-poorten: 16. Full duplex. MAC-adrestabel: 8000 entries, Switchingcapaciteit: 32 Gbit/s. Netwerkstandaard: IEEE 802.1Q, IEEE 802.1p, IEEE 802.3, IEEE 802.3ab, IEEE 802.3u. DC voltage input: 9 V. Ophangstelsysteem voor aan de muur



Beheerfuncties		Data-uitwisseling	
Switch type *	Unmanaged	Packet buffergeheugen	4,1 MB
Quality of Service (QoS)	✓	Beveiliging	
Poorten & interfaces		IGMP snooping	✓
Aantal basis-switching RJ-45 Ethernet-poorten *	16	Bescherming lus	✓
Type basis-switching RJ-45 Ethernet-poorten *	Gigabit Ethernet (10/100/1000)	Design	
Aantal Gigabit Ethernet (koper)-poorten	16	Stapelbaar *	✓
Netwerk		Kleur van het product	Zwart
Netwerkstandaard *	IEEE 802.1Q, IEEE 802.1p, IEEE 802.3, IEEE 802.3ab, IEEE 802.3u	Materiaal behuizing	Metaal
Koperen ethernetbekabelingstechnologie	10BASE-T, 100BASE-TX, 1000BASE-T	LED-indicatoren	✓
Ondersteunde kabel types	Cat3, Cat4, Cat5, Cat5e, Cat6	Ophangstelsysteem voor aan de muur	✓
Port mirroring	✓	Energie	
Full duplex	✓	Vermogenstoever inclusief *	✓
Datastroombeheer	✓	AC-ingangsspanning	220 V
Verbindingsaggregatie	✓	AC-ingangsfrequentie	50 Hz
Broadcast stormbeheer	✓	DC voltage input	9 V
Rate limiting	✓	Stroom	0.6 A
Auto MDI/MDI-X	✓	Stroomverbruik (typisch)	11,72 W
Auto-negotiation	✓	Vermogensverbruik (max)	144,28 W
Kabellengtedetectie	✓	Power over Ethernet (PoE)	
VLAN=ondersteuning	✓	Power over Ethernet (PoE) *	✗
Virtuele LAN-functies	Protocol-based VLAN, Tagged VLAN	Eisen aan de omgeving	
Aantal VLANs	32	Bedrijfstemperatuur (T-T)	0 - 40 °C
Data-uitwisseling		Temperatuur bij opslag	-40 - 70 °C
Switchingcapaciteit *	32 Gbit/s	Relatieve vochtigheid in bedrijf (V-V)	10 - 90 procent
Verzending snelheid	23,81 Mpps	Luchtvochtigheid bij opslag	5 - 90 procent
MAC-adrestabel *	8000 entries	Warmtedissipatie	490,55 BTU/h
Store-and-forward	✓	Gewicht en omvang	
Aantal wachtrijen	4	Breedte	286 mm
		Diepte	111,7 mm

Data-uitwisseling		Gewicht en omvang	
Jumbo Frames ondersteuning	✓	Hoogte	25,4 mm
Jumbo frames	9000	Verpakking	
		Meegeleverde kabels	AC
		Snelstartgids	✓



4895252500318



0840030708398



840030708398



4895252500301

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.