



TP-Link Omada SG3452XP netwerk-switch Managed L2+ Gigabit Ethernet (10/100/1000) Power over Ethernet (PoE) 1U Zwart

Merk : TP-Link

Productfamilie: Omada

Artikelcode: SG3452XP

Productnaam : SG3452XP



TP-Link Omada SG3452XP. Switch type: Managed, Switch-laag: L2+. Type basis-switching RJ-45 Ethernet-poorten: Gigabit Ethernet (10/100/1000), Aantal basis-switching RJ-45 Ethernet-poorten: 48, Console port: RJ-45/Micro-USB. MAC-adrestabel: 16000 entries, Switchingcapaciteit: 176 Gbit/s. Netwerkstandaard: IEEE 802.1D, IEEE 802.1Q, IEEE 802.1s, IEEE 802.1w, IEEE 802.3ab, IEEE 802.3ae, IEEE 802.3af, IEEE... Netstekker: AC-in-aansluiting. Power over Ethernet (PoE). Rack-montage, Vormfactor: 1U

Beheerfuncties		Beveiliging	
Switch type *	Managed	SSH/SSL support	✓
Switch-laag	L2+	BPDU filtering / bescherming	✓
Quality of Service (QoS)	✓	IP-MAC-Port binding	✓
Web-gebaseerd management	✓	Authenticatie	Auto VLAN, Gast-VLAN
Cloud-beheerd	✓	Multicast-functies	
ARP-inspectie	✓	Multicast-ondersteuning	✓
Locatie-instellingen (CLI) configureren	✓	Design	
System event log	✓	Rack-montage *	✓
Poorten & interfaces		Vormfactor	1U
Aantal basis-switching RJ-45 Ethernet-poorten *	48	Kleur van het product	Zwart
Type basis-switching RJ-45 Ethernet-poorten *	Gigabit Ethernet (10/100/1000)	Reset button	✓
Aantal moduleslots SPF+	4	LED-indicatoren	✓
Console port	RJ-45/Micro-USB	Aantal ventilatoren	3 ventilator(en)
Netstekker	AC-in-aansluiting	Certificering	CE, FCC, RoHS
Netwerk		Energie	
Netwerkstandaard *	IEEE 802.1D, IEEE 802.1Q, IEEE 802.1s, IEEE 802.1w, IEEE 802.3ab, IEEE 802.3ae, IEEE 802.3af, IEEE 802.3at, IEEE 802.3i, IEEE 802.3u, IEEE 802.3z	Stroombron *	AC
10G support *	✓	Vermogenstoevoer inclusief *	✓
Port mirroring	✓	AC-ingangsspanning	100 - 240 V
Datastroombeheer	✓	AC-ingangsfrequentie	50/60 Hz
Verbindingsaggregatie	✓	Vermogensverbruik (max)	635,7 W
Broadcast stormbeheer	✓	Power over Ethernet (PoE)	
Rate limiting	✓	Power over Ethernet (PoE) *	✓
Spanning tree protocol	✓	Aantal Power over Ethernet plus (PoE +)-poorten	48
Head-of-line (HOL) blocking	✓	Vermogen per poort Power over Ethernet (PoE)	30 W
VLAN=ondersteuning	✓	Totaal Power over Ethernet (PoE)-budget	500 W
Data-uitwisseling		Eisen aan de omgeving	
Switchingcapaciteit *	176 Gbit/s	Bedrijfstemperatuur (T-T)	0 - 40 °C
Verzending snelheid	130,9 Mpps	Temperatuur bij opslag	-40 - 70 °C
MAC-adrestabel *	16000 entries	Relatieve vochtigheid in bedrijf (V-V)	10 - 90 procent
Store-and-forward	✓	Luchtvochtigheid bij opslag	5 - 90 procent
Jumbo Frames ondersteuning	✓	Warmtedissipatie	2169,2 BTU/h
Jumbo frames	9000	Gewicht en omvang	
Packet buffergeheugen	12 MB	Breedte	440 mm
Beveiliging		Diepte	330 mm
DHCP-functies	DHCP client, DHCP relay, DHCP server	Hoogte	44 mm
Access Control List (ACL)	✓	Verpakking	
		Meegeliverde kabels	AC

Beveiliging		Verpakking	
IGMP snooping	✓	Snelstartgids	✓
MAC adres filtering	✓		
Statische poort beveiliging	✓		



6935364006495

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 12-APR-2024. Prints or copies of Information are only valid on the printed Publication date