



TP-Link Omada SL2428P netwerk-switch Managed L2 Fast Ethernet (10/100) Power over Ethernet (PoE) 1U Zwart

Merk : TP-Link

Productfamilie: Omada

Artikelcode: SL2428P

Productnaam : SL2428P



TP-Link Omada SL2428P. Switch type: Managed, Switch-laag: L2. Type basis-switching RJ-45 Ethernet-poorten: Fast Ethernet (10/100), Aantal basis-switching RJ-45 Ethernet-poorten: 24. MAC-adrestabel: 8000 entries, Switchingcapaciteit: 12,8 Gbit/s. Netwerkstandaard: IEEE 802.1D, IEEE 802.1Q, IEEE 802.1p, IEEE 802.1s, IEEE 802.1w, IEEE 802.3ab, IEEE 802.3ad, IEEE.... Power over Ethernet (PoE). Rackmontage, Vormfactor: 1U

Beheerfuncties		Beveiliging	
Switch type *	Managed	Ondersteunde beveiligingsalgoritmen	SNMPv2, SNMPv3, SSH, SSH-2, SSL/TLS
Switch-laag	L2	SSH/SSL support	✓
Quality of Service (QoS)	✓	Multicast-functies	
Web-gebaseerd management	✓	Multicast-ondersteuning	✓
ARP-inspectie	✓	Protocollen	
Locatie-instellingen (CLI) configureren	✓	Beheerprotocollen	SNMP v1/v2c/v3, RMON, SNMP, TFTP
System event log	✓	Design	
Poorten & interfaces		Rack-montage *	✓
Aantal basis-switching RJ-45 Ethernet-poorten *	24	Vormfactor	1U
Type basis-switching RJ-45 Ethernet-poorten *	Fast Ethernet (10/100)	Kleur van het product	Zwart
Fast Ethernet (koperen) ports kwantiteit	24	Aantal ventilatoren	2 ventilator(en)
Aantal Gigabit Ethernet (koper)-poorten	4	Certificering	CE, FCC, RoHS
Aantal Combo SFP-poorten	2	Prestatie	
Netwerk		Compatibele besturingssystemen	Microsoft Windows XP, Vista, Windows 7, Windows 8, MAC OS, NetWare, UNIX, Linux
Netwerkstandaard *	IEEE 802.1D, IEEE 802.1Q, IEEE 802.1p, IEEE 802.1s, IEEE 802.1w, IEEE 802.3ab, IEEE 802.3ad, IEEE 802.3af, IEEE 802.3at, IEEE 802.3i, IEEE 802.3u, IEEE 802.3x	Upgraden van firmware mogelijk	✓
10G support *	✗	Energie	
Koperen ethernetbekabelingstechnologie	10BASE-T, 100BASE-TX, 1000BASE-T	Stroombron *	AC
Ondersteundende kabel types	Cat5, Cat5e	AC-ingangsspanning	100 - 240 V
Port mirroring	✓	AC-ingangsfrequentie	50/60 Hz
Datastroombeheer	✓	Vermogensverbruik (max)	291,6 W
Verbindingsaggregatie	✓	Power over Ethernet (PoE)	
Broadcast stormbeheer	✓	Power over Ethernet (PoE) *	✓
Rate limiting	✓	Aantal Power over Ethernet plus (PoE +)-poorten	24
Auto MDI/MDI-X	✓	Totaal Power over Ethernet (PoE)-budget	250 W
Spanning tree protocol	✓	Eisen aan de omgeving	
VLAN=ondersteuning	✓	Bedrijfstemperatuur (T-T)	0 - 40 °C
Aantal VLANs	512	Temperatuur bij opslag	-40 - 70 °C
Data-uitwisseling		Relatieve vochtigheid in bedrijf (V-V)	10 - 90 procent
Switchingcapaciteit *	12,8 Gbit/s	Luchtvochtigheid bij opslag	5 - 90 procent
Throughput	9,5 Mpps	Warmtedissipatie	995,09 BTU/h
MAC-adrestabel *	8000 entries	Gewicht en omvang	
Aantal wachtrijen	4	Breedte	440 mm
Jumbo Frames ondersteuning	✓	Diepte	180 mm
Jumbo frames	9000	Hoogte	44 mm
Packet buffergeheugen	4,1 MB		

Beveiliging		Verpakking	
Access Control List (ACL)	✓	Meegeleverde kabels	AC
IGMP snooping	✓	Snelstartgids	✓
		Rekbevestigingspakket	✓



6935364030612

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 17-MAY-2024. Prints or copies of Information are only valid on the printed Publication date