
ROLINE HDMI over IP Extender, 4K30Hz, 120m, W/IR

Product No. 14.01.3642

Manufacturer ROLINE

Manufacturer No. 14.01.3642











With this HDMI over IP Extender, you can extend HDMI signals up to 120 m with 4K@30Hz via a network cable of Cat. 5e or higher. An ideal solution for sharing a screen or projector over a LAN network. IR signals from a remote control of the video source can also be redirected - perfect for controlling your video source from your video destination.

Suitable for advertising, studios, multimedia classrooms, etc.

- Following TCP/IP standard
- Supports resolutions up to 4K@30Hz
- Max. distance is 120m
- Supports max video bandwidth of 3.4Gbps/340MHz per channel (10.2 Gbps all channels)
- Cat5e/6 cable needs to follow the standard of IEEE-568B
- Features IR return, which enables you to control the video source from your video destination
- Features 2 extension modes: simple mode (1:1) and allocation mode (1:N)
- Stable metal casing
- Dimensions: TX/RX: 24 x 94 x 120 mm
- Weight: TX/RX: 214 g
- Contents: 1x Transmitter, 1x Receiver, 2x Power Supply (TX: 1x 5 VDC 1A, RX: 1x 5 VDC 1A), User Manual

Technical specifications	
Manufacturer	ROLINE
Product group	Splitters and selectors
Product type	HDMI Extender
Colour	black
Scope of delivery	1x Transmitter, 1x Receiver, 2x Power Supply (TX: 1x 5 VDC 1A, RX: 1x 5 VDC 1A), User Manual
Interface	НДМІ
Inputs	1
Outputs	1
Max. distance	120 m
Video input	НДМІ
Video output	HDMI
Video band width	10.2 Gbps
Max. resolution	3840 x 2160 @30Hz (4K, Full HD)
Dimensions (HxWxD)	TX: 24 x 94 x 120 mm, RX: 24 x 94 x 120 mm
Power supply unit	2x
Power supply output	TX: DC 5V 1A, RX: DC 5V 1A
Technical particularity	Extends the signal up to 120m
Operating temperature min.	0 °C
Operating temperature max.	50 °C
Height	24 mm
Width	94 mm
Depth	120 mm
Weight	428 g
Height of packaging (single piece)	0 mm
Width of packaging (single piece)	0 mm

Depth of packaging (single piece)	0 mm
Package weight (single piece)	0 kg