## **ROLINE 19-inch wall-mounted housing Pro 22 U,** 600x600 WxD IP55 outdoor grey

Product No. Manufacturer Manufacturer No. EAN (single piece) 26.21.0092 ROLINE 26.21.0092 7630049600935









## 19 inch wall-mounted housing Pro 22 U 600x600 WxD IP55 outdoor grey

The outdoor network enclosures for wall mounting are developed in accordance with protection class IP55 and are specially designed for use in harsh environments, particularly outdoors. The wall-mounted enclosures offer a 3-point locking system with lockable swivelling handle and insulated PG cable glands. Integrated ventilation filter housings ensure ventilation and provide protection against water and dust in accordance with IP54. These enclosures are ideal for outdoor areas that are exposed to environmental influences such as rain, hail and splash water. The roof chassis is equipped with a filtered area for the installation of a fan module. Inside there is a pair (from 600 mm depth two pairs) of galvanised 19" profile rails, which can be read in both directions and are adjustable in depth. Each cabinet consists of a robust steel construction with a material thickness of up to 2.0 mm.

Technical specifications		
Manufacturer	ROLINE	
Product group	19"- / 10" technology	
Product type	19"-Outdoor wall housing	
Colour	grey	
Scope of delivery	19-inch wall-mounted housing Pro 22 U, earthing cable set, 2x spanners, installation set (screws, cage nuts, washers)	

Type of profile rail	L-shaped
Modular spacing	482.6 mm (19 inch)
Model	With permanent frame
Height units	22 U
Minimum rack depth supported	260 mm
Maximum rack depth supported	535 mm
Delivery condition	fully assembled
Demountable	no
Material group	Steel
Material front door	Steel
Wall mountable	yes
Adjustable feets	no
Maximum weight capacity	100 kg
Protection class (IP Code)	IP55
Soundproof	no
Number of doors	1
With front door	yes
With backside door	no
With glazed door	no
Front	Steel door
Rack rails	no
Side panels included	no
Removeable side panels	no
Removable front door	yes
Removable back door	no
Ventilation	Passive
RAL colour	RAL 7035 Light grey

1157 mm
600 mm
600 mm
61 kg
1180 mm
690 mm
630 mm
64.1 kg