## ROLINE 19-inch server rack 42 U, 600x1200 WxD grey

**Product No.** 26.21.0155

ROLINE

Manufacturer No. 26.21.0155

**EAN (single piece)** 7630049601581



Manufacturer





## ROLINE 19 inch server cabinet 42 U 600x1200 WxD grey

The server enclosures in the ROLINE Pro series have been specially developed for convenient and flexible network cabling. Inlets with brushes, a slide-on inlet with a foam rubber seal and an additional brush inlet in the base chassis are located on the sides of the roof and base (from 800 mm enclosure width), offering a wide range of possible applications. Perforated single-leaf front doors and double-leaf rear doors, each with a swivel handle and profile half cylinder, ensure improved air circulation. The roof has a perforated cover that allows easy installation of a fan module.

Two pairs of galvanised 19" profile rails are mounted inside the cabinet, which are equipped with height units that can be read in both directions and are adjustable in depth. They are also connected with depth braces. Each cabinet consists of a robust steel construction with a material thickness of up to 2.0 mm. The cabinets are electrostatically powder-coated and available in the standard colours grey (RAL 7035) and black (RAL 9005). Modular lockable and removable side panels (horizontally divided from 42U) and doors improve accessibility. The door hinges can also be changed. The entire construction can be dismantled, meaning that the cabinets can be completely removed if required.

	Technical specifications
Manufacturer	ROLINE
Product group	19"-/10"-Cabinet
Product type	19"-Server cabinet
Colour	grey

nch server enclosure 42 U, earthing cable set, installation or profile half cylinder, 2x spanners, installation set ews, cage nuts, washers), assembly instructions  mm  assembled  bl door with perferation
mm assembled el
mm assembled el
assembled el 0 kg
0 kg
0 kg
al door with porforation
door with portoration
el door with perforation
sive
7035 Light grey
0 mm
mm
0 mm
.5 kg

Width of packaging (single piece)	680 mm
Depth of packaging (single piece)	1280 mm
Package weight (single piece)	123 kg