

ROLINE 19-inch wall-mounted housing Pro 20 U, 600x450 WxD black

Product No.	26.21.0178
Manufacturer	ROLINE
Manufacturer No.	26.21.0178
EAN (single piece)	7630049601819



ROLINE 19 inch wall-mounted housing Pro 20 U 600x450 WxD black

The wall-mounted enclosures in the ROLINE Pro series have been specially designed for flexible network cabling. Each enclosure has a slide-on cable inlet in the roof with a foam rubber seal. The rear panel and the base plate are equipped with punched cable inlets and plastic covers. The roof chassis has a punched-out area to accommodate a fan module. Inside, two pairs of galvanised profile rails with height units of 483 mm (19") are installed, which are also adjustable in depth. The robust steel constructions of the cabinets are made of up to 1.5 mm thick sheet steel and are available powder-coated in grey (RAL 7035) or black (RAL 9005). The side panels and front door are modular, lockable and removable, which improves accessibility. Wall mounting is carried out in two simple steps: Firstly, the rear panel is screwed to the wall and then connected to the housing. Optional levelling feet or castors can be used to make the enclosures free-standing.

Technical specifications

Manufacturer	ROLINE
Product group	19"- / 10" technology
Product type	19"-wall housing
Colour	black

Scope of delivery	19-inch wall-mounted enclosure Pro 20 U, earthing cable set, installation set (screws, cage nuts, washers), 2x spanners, assembly instructions
Height units	20 U
Minimum rack depth supported	305 mm
Maximum rack depth supported	370 mm
delivery condition	fully assembled
Material group	Steel
Wall mountable	yes
Adjustable feet	no
Protection class (IP Code)	IP20
Soundproof	no
Front	Glass door
Rack rails	yes
Side panels included	yes
Removeable side panels	yes
Removable front door	yes
Removable back door	no
Ventilation	Passive
RAL colour	RAL 9005 Jet black
Height	996 mm
Width	450 mm
Depth	600 mm
Weight	35 kg
Height of packaging (single piece)	1050 mm
Width of packaging (single piece)	660 mm

Depth of packaging (single piece)	520 mm
--------------------------------------	--------

Package weight (single piece)	38 kg
----------------------------------	-------