VALUE HDMI Matrix Switch, 4x4, 4K60Hz, with remote control

Product No. 14.99.3593


Manufacturer VALUE


Manufacturer No. 14.99.3593

EAN (single piece) 7630049633360















This 4 in 4 out HDMI Matrix can switch 4 HDMI input signals (PC, notebook, etc.) to 4 HDMI displays (monitor, projector, etc.) with resolutions up to 4096x2160@60Hz. It supports multiple switching methods (buttons on the matrix, IR remote control and RS232). Any two of the four HDMI outputs support automatic down-scaling. This matrix can be used in security surveillance, education, training, exhibitions, trade shows, broadcasting, command centers and many other applications.

- Four HDMI input signals can be switched to four HDMI output devices
- Up to 4K (4096 x 2160 @60Hz) resolution and backwards compatible
- Compatible with HDCP 2.2 and HDCP 1.4
- Any two of the four HDMI outputs support auto down-scaling.
- Supported digital audio formats: DTS-HD/Dolby-TrueHD/LPCM7.1/DTS/Dolby-Atmos
- Input devices can be switched by push buttons on the switch, IR remote control or by RS-232
- 16 different EDID states / resolutions can be set with the DIP switch
- Contents: HDMI Matrix Switch, Power Supply, Remote Control, Mounting Ears (2x), Terminal Block, User Manual

Technical specifications		
Manufacturer	VALUE	
Product group	Splitters and selectors	
Product type	HDMI-Matrix-Switch 4K	
Colour	black	
Scope of delivery	HDMI Matrix Switch, Power Supply, Remote Control, Mounting Ears (2x), Terminal Block, User Manual	
Interface	HDMI	
Inputs	4	
Outputs	4	
Video input	4x HDMI Female	
Video output	4x HDMI Female	
Video band width	18 Gbps	
Max. resolution (nom.)	4096 x 2160 @60Hz (4K)	
Max. resolution	4096 x 2160 @60Hz (4K)	
Dimensions (HxWxD)	21 x 210 x 80 mm	
Power supply output	5V DC, 1A	
Technical particularity	Switching via push buttons, via IR remote control or via RS-232	
Operating temperature min.	-20 °C	
Operating temperature max.	60 °C	
Storage temperature min.	-30 °C	
Storage temperature max.	70 °C	
Height	21 mm	
Width	210 mm	
Depth	80 mm	
Weight	375 g	

Height of packaging (single piece)	90 mm
Width of packaging (single piece)	180 mm
Depth of packaging (single piece)	250 mm
Package weight (single piece)	0.7 kg