ROLINE RM UTP Patch Cord Cat.6A, white, 5 m

Product No. 21.45.3165

rolline recycled material


Manufacturer ROLINE RECYCLED MATERIAL

Manufacturer No. 21.45.3165

EAN (single piece) 7630049631113











Unshielded, pre-assembled category 6A network cable with RJ-45 plugs at both ends. The patch cable from our ROLINE Recycled Material product line is suitable as a patch cable in patch panels or as a device connection cable and is intended for use in local networks.

- Patch cable for networking connections between devices
- Prepared unshielded Twisted Pair cable with RJ-45 connectors on both ends
- Durable due to moulded kink protection
- Flexible cable, suitable for narrow bending
- High quality plugs with gold plated contacts
- Contact settings 1:1, in accordance with the EIA/TIA 568 standard
- Construction: 4-pair stranded copper wire

ROLINE RECYCLED MATERIAL products consist of more than 50% recycled materials. The packaging is even made from 100% recycled material.

| Technical specifications | | |
|--------------------------|--------------------------|--|
| Manufacturer | ROLINE RECYCLED MATERIAL | |
| Product group | Twisted Pair Cable | |
| Product type | UTP Patch Cables | |

| Colour | white |
|------------------------------------|------------------|
| Length | 5 m |
| Shield type | UTP |
| Transfer quality | Cat6A / Class EA |
| Component-Level certified | yes |
| Quantity of wires | 8 |
| Conductor type | Wire |
| Crossed | no |
| Locking lever | yes |
| Anti-kink sleeve | Moulded-on |
| Colour (Spout) | white |
| Side 1 Connector Type | RJ-45 |
| Side 1 Connector Gender | Male |
| Side 2 Connector Type | RJ-45 |
| Side 2 Connector Gender | Male |
| Connector Type RJ45 | Standard |
| Operating temperature min. | -20 °C |
| Operating temperature max. | 75 °C |
| Storage temperature min. | -20 °C |
| Storage temperature max. | 80 °C |
| Weight | 116.9 g |
| Height of packaging (single piece) | 20 mm |
| Width of packaging (single piece) | 120 mm |
| | |

| Depth of packaging (single piece) | 150 mm |
|-----------------------------------|---------|
| Package weight (single piece) | 0.12 kg |