

ROLINE RM S/FTP (PiMF) Patch Cord Cat.6A, red, 20 m

| | |
|---------------------------|--------------------------|
| Product No. | 21.45.3219 |
| Manufacturer | ROLINE RECYCLED MATERIAL |
| Manufacturer No. | 21.45.3219 |
| EAN (single piece) | 7630049631373 |



The patch cables in the **ROLINE RECYCLED MATERIAL** product line with shielded **RJ-45** connectors are ideal for **10 Gigabit Ethernet** networks. **Gold-plated contacts** and **moulded bend protection** ensure **durability** and **reliable performance**.

- Patch cable for networking connections between devices
- Prepared double shielded Twisted Pair cable with screened RJ-45 connectors on both ends
- Durable due to moulded kink protection
- Flexible cable, suitable for narrow bending
- High quality plugs with gold plated contacts
- Contact settings 1:1, in accordance with the EIA/TIA 568 standard
- Construction: 4-pair stranded copper wire
- Complete braid shielding. Pairs shielded with aluminium clad polyester foil

ROLINE RECYCLED MATERIAL products consist of more than **50% recycled materials**. The packaging is even made from **100% recycled material**.

Technical specifications

| | |
|---------------|--------------------------|
| Manufacturer | ROLINE RECYCLED MATERIAL |
| Product group | Twisted Pair Cable |
| Product type | S/FTP Patchcord |

| | |
|------------------------------------|------------------|
| Colour | red |
| Length | 20 m |
| Shield type | SFTP |
| Transfer quality | Cat6A / Class EA |
| Quantity of wires | 8 |
| Conductor type | Wire |
| Crossed | no |
| Locking lever | yes |
| Anti-kink sleeve | Moulded-on |
| Side 1 Connector Type | RJ-45 |
| Side 1 Connector Gender | Male |
| Side 2 Connector Type | RJ-45 |
| Side 2 Connector Gender | Male |
| Connector Type RJ45 | Standard |
| Operating temperature min. | -20 °C |
| Operating temperature max. | 75 °C |
| Storage temperature min. | -20 °C |
| Storage temperature max. | 80 °C |
| Weight | 587.4 g |
| Height of packaging (single piece) | 60 mm |
| Width of packaging (single piece) | 180 mm |
| Depth of packaging (single piece) | 180 mm |

Package weight (single piece) 0.6 kg