

# ROLINE RM S/FTP (PiMF) Patch Cord Cat.6A, white, 2 m

<b>Product No.</b>	21.45.3262
<b>Manufacturer</b>	ROLINE RECYCLED MATERIAL
<b>Manufacturer No.</b>	21.45.3262
<b>EAN (single piece)</b>	7630049631861



**The patch cables in the ROLINE RECYCLED MATERIAL product line with shielded RJ-45 connectors are ideal for 10 Gigabit Ethernet networks. Gold-plated contacts and moulded bend protection ensure durability and reliable performance.**

- Patch cable for networking connections between devices
- Prepared double shielded Twisted Pair cable with screened RJ-45 connectors on both ends
- Durable due to moulded kink protection
- Flexible cable, suitable for narrow bending
- High quality plugs with gold plated contacts
- Contact settings 1:1, in accordance with the EIA/TIA 568 standard
- Construction: 4-pair stranded copper wire
- Complete braid shielding. Pairs shielded with aluminium clad polyester foil

**ROLINE RECYCLED MATERIAL products consist of more than 50% recycled materials. The packaging is even made from 100% recycled material.**

## Technical specifications

Manufacturer	ROLINE RECYCLED MATERIAL
Product group	Twisted Pair Cable

Product type	S/FTP Patchcord
Colour	white
Length	2 m
Shield type	SFTP
Transfer quality	Cat6A / Class EA
Quantity of wires	8
Conductor type	Wire
Crossed	no
Locking lever	yes
Anti-kink sleeve	Moulded-on
Side 1 Connector Type	RJ-45
Side 1 Connector Gender	Male
Side 2 Connector Type	RJ-45
Side 2 Connector Gender	Male
Connector Type RJ45	Standard
Operating temperature min.	-20 °C
Operating temperature max.	75 °C
Storage temperature min.	-20 °C
Storage temperature max.	80 °C
Weight	66.5 g
Height of packaging (single piece)	20 mm
Width of packaging (single piece)	100 mm
Depth of packaging (single piece)	100 mm

Package weight (single piece) 0.075 kg