## ROLINE RM U/FTP DataCenter Patch Cord Cat.6A (Class EA), slim, black, 2 m

**Product No.** 21.45.3355

ROLINE RECYCLED MATERIAL


Manufacturer No. 21.45.3355

**EAN (single piece)** 7630049630284



Manufacturer





roline 🚐







Category 6a twisted-pair patch cable with shielded RJ-45 connectors on both sides. Particularly thin and flexible cable from our ROLINE Recycled Material product line with individual pairs of wires in aluminium-laminated foil for use in confined spaces, such as in data centres.

- Durable thanks to moulded-on kink protection
- Suitable as patch cable in patch panels or as device connection cable and intended for use in the LAN
- Contact assignment: 1:1 according to EIA/TIA568, 8 cores
- Structure: 8 cores stranded wire, pairs shielded with alu-laminated foil

## ROLINE RECYCLED MATERIAL products consist of more than 50% recycled materials. The packaging is even made from 100% recycled material.

| Technical specifications |                          |  |
|--------------------------|--------------------------|--|
| Manufacturer             | ROLINE RECYCLED MATERIAL |  |
| Product group            | Twisted Pair Cable       |  |
| Product type             | FTP Patch Cord           |  |

| Colour                             | black            |
|------------------------------------|------------------|
| Length                             | 2 m              |
| Shield type                        | FTP              |
| Transfer quality                   | Cat6A / Class EA |
| Quantity of wires                  | 8                |
| Conductor type                     | Wire             |
| Crossed                            | no               |
| Slim cable                         | yes              |
| Locking lever                      | yes              |
| Anti-kink sleeve                   | Moulded-on       |
| Side 1 Connector Type              | RJ-45            |
| Side 1 Connector<br>Gender         | Male             |
| Side 2 Connector Type              | RJ-45            |
| Side 2 Connector<br>Gender         | Male             |
| Connector Type RJ45                | Standard         |
| Operating temperature min.         | -20 °C           |
| Operating temperature max.         | 75 °C            |
| Storage temperature min.           | -20 °C           |
| Storage temperature max.           | 80 °C            |
| Weight                             | 35.1 g           |
| Height of packaging (single piece) | 20 mm            |
| Width of packaging (single piece)  | 100 mm           |
| Depth of packaging (single piece)  | 120 mm           |
|                                    |                  |

Package weight (single 0.044 kg piece)