

# ROLINE RM UTP Data Center Patch Cord Cat.6A (Class EA), Slim, blue, 0.3 m

|                           |                          |
|---------------------------|--------------------------|
| <b>Product No.</b>        | 21.45.3441               |
| <b>Manufacturer</b>       | ROLINE RECYCLED MATERIAL |
| <b>Manufacturer No.</b>   | 21.45.3441               |
| <b>EAN (single piece)</b> | 7630049629608            |



**Category 6A twisted-pair patch cable with RJ-45 connectors on both sides. Particularly thin and flexible cable from our ROLINE Recycled Material product line with individual pairs of wires for use in confined spaces, such as in data centres.**

- Durable thanks to moulded-on kink protection
- Suitable as patch cable in patch panels or as device connection cable and intended for use in the LAN
- Contact assignment: 1:1 according to EIA/TIA568, 8 cores
- Structure: 8 cores stranded wire

**ROLINE RECYCLED MATERIAL products consist of more than 50% recycled materials. The packaging is even made from 100% recycled material.**

## Technical specifications

|               |                          |
|---------------|--------------------------|
| Manufacturer  | ROLINE RECYCLED MATERIAL |
| Product group | Twisted Pair Cable       |
| Product type  | UTP Patch Cables         |
| Colour        | blue                     |

|                                    |                  |
|------------------------------------|------------------|
| Length                             | 0.3 m            |
| Shield type                        | UTP              |
| Transfer quality                   | Cat6A / Class EA |
| Quantity of wires                  | 8                |
| Conductor type                     | Wire             |
| Crossed                            | no               |
| Slim cable                         | yes              |
| Locking lever                      | yes              |
| Anti-kink sleeve                   | Moulded-on       |
| External cable diameter            | 3.4 +/- 0.2mm    |
| Side 1 Connector Type              | RJ-45            |
| Side 1 Connector Gender            | Male             |
| Side 2 Connector Type              | RJ-45            |
| Side 2 Connector Gender            | Male             |
| Connector Type RJ45                | Standard         |
| Operating temperature min.         | -20 °C           |
| Operating temperature max.         | 75 °C            |
| Storage temperature min.           | -20 °C           |
| Storage temperature max.           | 80 °C            |
| Weight                             | 8.5 g            |
| Height of packaging (single piece) | 10 mm            |
| Width of packaging (single piece)  | 10 mm            |
| Depth of packaging (single piece)  | 50 mm            |

Package weight (single piece) 0.012 kg